

ALEXIA 995




cheminée bois centrale

central woodburning fireplace

zentraler Holzkamin

caminetto a legna centrale



gris anthracite

anthracite grey / Anthrazit grau / grigio antracite



noir

black / Schwarz / nero



chocolat


chocolate / Schokoladenbraun / cioccolato




taupe

platinum / Taupe / talpa

Vue de face
[face view / Frontansicht / Vista frontale]




Vue de dessus
[top view / Draufsicht / Vista dall'alto]




A
Hauteur sous plafond adaptable
Adjustable ceiling height
Variable Deckenhöhe
Altezza soffitto adattabile

Vue de face
[face view / Frontansicht / Vista frontale]



Vue de dessus
[top view / Draufsicht / Vista dall'alto]



A	D
Hauteur sous plafond adaptable	Vitre
Adjustable ceiling height	Glass
Variable Deckenhöhe	Glas
Altezza soffitto adattabile	Vetro

	FOYER FERME CLOSED FIREPLACE / GESCHLOSSENE FEUERSTELLE / FOCOLARE CHIUSO
	ALEXIA 995 CFF
Puissance nominale / <i>nominal output / durchschnittliche Nennwärmeleistung / Potenza termica nominale</i>	11,0 kW
Puissance thermique émise dans la pièce / <i>Useful thermal power emitted in the room / Nutzbare Nennwärme/ Potenza termica utile emessa nella stanza</i>	11,0 kW
Rendement énergétique / <i>Energy efficiency / Wirkungsgrad / Rendimento</i>	80,2%
Emission CO (%CO à 13% O2) / <i>CO emission (13% O2) / CO-Emission / Emissioni CO (%CO a 13% O2)</i>	0,08%
Emission Particules - poussières (mg/Nm³ à 13% O2) / <i>Particles - Dust emission (mg/Nm³ at 13% O2) / Fein-staub mg/Nm³ bei 13%O2 / Emissioni Polveri sottili (mg/Nm³ a 13% O2)</i>	38 mg/Nm³
Oxyde d'azote (NOx) à 13% O2 (mg/Nm³) / <i>Nitrogen oxide (NOx) at 13% O2 (mg/Nm³) / Stickstoff (NOx) bei 13% O2 (mg/Nm³) / Ossido di azoto (NOx) a 13% O2 (mg/Nm³)</i>	48 mg/Nm³
Composés Organiques Volatils (COV) à 13% O2 / <i>Organic Gazeus Compounds (OGC) at 13% O2 / organische Gaskomponenten (OGC) bei 13% O2 / Composti organici volatili (COV) a 13% O2</i>	288 mg/Nm³
Emissions de CO2 / <i>CO2 emission / CO-2-Emission / Emissioni di CO2</i>	10,50%
Température des fumées / <i>Smoke temperature / Abgastemperatur / Temperatura fumi</i>	271°C
Température des fumées en sortie de buse / <i>Smoke temperature at the nozzle outlet / Abgastemperatur am Stutzen / Temperatura fumi all'uscita del raccordo</i>	325°C
Tirage minimum - tirage nominal / <i>Minimum draft - Nominal draft / Förderdruck / Tiraggio minimo - Tiraggio nominale</i>	12 Pa
Dimensions / <i>Dimensions / Abmessungen / Dimensioni</i>	Ø 118 cm XL Ø 95 cm
Dimension bûche maxi / <i>Logs' maximum lengths / max. Holzscheitlänge / Lunghezza massima dei ceppi</i>	50 cm
Charge de bois conseillée <i>Recommended wood load empfohlene Holzaufgabemenge Carica legna consigliata</i>	5 bûches de 950 gr L 33 cm fendues en 1/4 <i>5 logs of 950gr, length 33cm, splitted in 1/4</i> <i>5 Holzscheite mit 950 Gramm, Länge 33 cm, geteilt in 4 Stücke</i> <i>5 ceppi da 950gr lunghezza 33cm spaccata in 1/4</i>
Conforme norme / <i>comply with norm / entspricht der Norm / Conforme alle norme</i>	EN13240
Sortie de fumée (verticale ou horizontale) <i>Smoke exit (vertical or horizontal) Rauchabgang (oben oder hinten) Uscita fumi (verticale o orizzontale)</i>	Verticale <i>Vertical Vertikal Verticale</i>
Débit massique des fumées / <i>Mass flow rate of smoke / Abgasmassenstrom / Portata in massa dei fumi</i>	16,3 g/s
Diamètre ou section d'évacuation des fumées (intérieur hotte) / <i>Smoke discharge diameter / Rauchabgang - Durchmesser / Diametro di evacuazione dei fumi</i>	236
Diamètre de raccordement / <i>Flue pipe diameter / Rauchrohrquerschnitt / Diametro del raccordo</i>	230
Diamètre d'entrée d'air / <i>Air inlet diameter / Frischluftzufuhrdurchmesser / Diametro entrata aria</i>	Ø125 au sol <i>on the floor im Fußboden a pavimento</i>
Section d'amenée d'air / <i>Air inlet diameter / Frischluftzuleitung (Fläche) / Sezione arrivo aria</i>	100 cm²
Masse de l'appareil seul / <i>mass of the unit / Gewicht / Peso del solo apparecchio</i>	65 kg
Masse de l'appareil seul lacqué / <i>mass of the lacquered finish unit / Gewicht lackiertes Modell / Peso del solo apparecchio laccato</i>	85 kg
Masse par mètre de prolongation supplémentaire / <i>Mass per meter of additional extension / Gewicht zusätzliche Rauchrohrverlängerung / Peso di un metro di tubo supplementare</i>	24 kg
Masse par mètre de prolongation supplémentaire lacquée / <i>Mass per meter of additional lacquered extension / Gewicht zusätzliche lackierte Rauchrohrverlängerung / Peso di un metro di tubo supplementare laccato</i>	30 kg
Étanche selon EN 16510-1 / <i>Airtight according to EN 16510-1 norm / Raumlufunabhängig gemäß EN16510-1 Norm / Ermetico secondo EN 16510-1</i>	NON / NO / NEIN / NO
Si étanche, fuite sous 10Pa selon EN 16510-1 / <i>If Airtight, leakage under 10Pa according to EN 16510-1 / Raumlufunabhängig unter 10Pa nach EN 16510-1 / Se ermetico, perdita sotto 10Pa secondo EN 16510-1</i>	/
Distance minimum entre les vitres de l'appareil et tous matériaux combustibles / <i>Minimum distance between the glass pane of the appliance and all combustible materials / Mindestabstand Glas zu brennbaren Materialien / Distanza minima tra i vetri dell'apparecchio e tutti i materiali combustibili</i>	1200 mm
Distance minimum entre le côté de l'appareil et tous matériaux combustibles / <i>Minimum distance between the side of the appliance and any combustible materials / Mindestabstand zwischen seitlicher Feuerstelle zu brennbaren Materialien / Distanza minima tra il lato dell'apparecchio e tutti i materiali combustibili</i>	1200 mm
Nature matériau mur pour mural ou angle <i>Nature of the wall for wall or corner-mounted units Beschaffenheit der Wand bei Wand-oder Eckmodellen Natura dei materiali della parete per caminetti a parete o ad angolo</i>	/
Distance minimum entre le bas de l'appareil et tous matériaux combustibles <i>Minimum distance between the bottom of the appliance and any combustible materials Mindestabstand zwischen dem Boden der Feuerstelle zu brennbaren Materialien Distanza minima tra la base dell'apparecchio e tutti i materiali combustibili</i>	Sur socle <i>on base mit Sockel Su basamento</i>