

FIREPLACE KIT SYSTEM FROM BRUNNER




BSK 11 mit Panorama-Kamin 70/25/40/25

State: 17.11.2016



BRUNNER[®]
made in germany.



Planning and installation

BSK 11 mit Panorama-Kamin 70/25/40/25

Tested according to

EN 13229

Data for functional demonstration

Rated heat power	kW	8
Firewood consumption	kg/h	2,4
Flue gas mass flow	g/s	7
Flue gas temperature	°C	210
Necessary supply pressure ¹⁾	Pa	12
Combustion air consumption	m³/h	22
Combustion air connection Ø	mm	125

Height extension rings

Ground area (width x depth)	mm	600 x 720
Overall height	mm	1856
Height extension ring	mm	250

Distances

Dist. to adjacent wall in direct contact (with radiation panels inside) ²⁾	cm	0
Dist. to adjacent wall for free-standing design (without radiation panels inside) ²⁾	cm	5
Distance to the ceiling	cm	50

Heat insulation

In ceiling region connection with/without air grate	cm	19 / 14
---	----	---------

Hot air cross section ³⁾

Supply air	cm²	723
Warm air	cm²	732

Weight

Total weight	kg	460
--------------	----	-----

meets requirement limit values for:

Germany / Austria / Switzerland / Norway

1.BImSchV (Stufe 2) / 15a BVG (2015) / LRV / -

1) Throttle flap recommended

2) Distance is valid for adjacent walls. For protected walls, a brick lining is required

3) Existing supply air opening

Ulrich Brunner GmbH
Zellhuber Ring 17 -18
D-84307 Eggenfelden
Telefon: +49 / (0)87 21 / 7 71-0
Telefax: +49 / (0)87 21 / 7 71-100
info@brunner.eu | www.brunner.eu

BRUNNER®