

Technical data

Technical data	operation when directly connected to chimney	operation when connected accumulation mass	
Energy label		----	----
Operating data			
Nominal heat power	7 kW	----	----
Efficiency	> 80 %	----	----
Consumption of wood	2,2 kg/h	3,5 kg	3,1 kg
Total heat output of the burning chamber	----	14 kW	12 kW
Average heat output / heat accumulation time ⁵	----	1,4 kW / 8 h	1,2 kW / 8 h
Mass flow of flue gas	7 g/s	12 g/s	11 g/s
Required chimney pressure	12 Pa	12 Pa	15 Pa
Required amount of combustion air	20 m³/h	30 m³/h	30 m³/h
Average flue gas temperature			
on the output	270 °C	350 °C	333 °C
behind 2,4 m of ceramic accumulation system KMS 240 ¹	----	210 °C	----
behind S-accumulation rings (5x S-acc. ring Ø345mm)	----	----	211 °C
Heat distribution			
fireplace insert	56–66 %	30 %	30 %
door glass (single / double)	44 / 0 %	44 / 0 %	44 / 0 %
additional accumulation mass	----	36–46 %	36–46 %
Information for ventilated builds			
Minimal grill area supply / outgoing	700 cm²	700 cm²	700 cm²
Minimum distance from insulated areas / floor	50 / 0 mm	50 / 0 mm	
Reference insulation ² ceiling / back wall / side wall / floor	120 / 70 / 0 / 0 mm	120 / 70 / 0 / 0 mm	
Calciumsilicate insulation ³ ceiling / back wall / side wall / floor	80 / 50 / 0 / 0 mm	80 / 50 / 0 / 0 mm	
Information for non-ventilated builds (closed grills)			
Minimum radiant area ⁴	suitable	3 m²	
Minimum distance from insulated areas / floor	50 / 20 mm	50 / 20 mm	
Reference insulation ² ceiling / back wall / side wall / floor	160 / 90 / 0 / 20 mm	160 / 90 / 0 / 20 mm	
Calciumsilicate insulation ³ ceiling / back wall / side wall / floor	120 / 70 / 0 / 20 mm	120 / 70 / 0 / 20 mm	
General technical information			
Total weight / lining weight	circa 155 / 40 kg	circa 155 / 40 kg	
Burning chamber dimensions (width x depth)	390 x 205 mm		
Combustion air connection	Ø 125 mm		
Use in non-ventilated accumulation builds according to craft rules	suitable		
Tested according to	EN 16510-1 ed. 2:2023, EN 16510-2-2:2022		
Meets values	1. BImSchV (Stufe2), 15a BVG		

¹ Listed value from testing. For accurate results is evaluation of each system in the Ortnr / KOV program necessary

² Mineral wool according to AGI-Q 132

³ Example SkamoEnclosure Board 225 kg/m³


⁴ Depends on accumulation period and material characteristics. Listed values calculated with average specific heat output = approx. 500 W/m²

⁵ Storage operation, one wood charge for storage duration, with closed construction and efficiency > 80%

UKA 35/60/35/50Sh

Technical data
Date 06/2026



UKA 35/60/35/50Sh / air inlet / feet



UKA 35/60/35/50Sh

Technical data
Date 06/2026


UKA 35/60/35/50Sh S-accumulation set




UKA 35/60/35/50Sh

Technical data
Date 06/2026

UKA 35/60/35/50Sh supporting construction incl. build-on frame 3sides 70 mm



UKA 35/60/35/50Sh supporting construction incl. build-on frame 5sides 70 mm



UKA 35/60/35/50Sh

Technical data
Date 06/2026

UKA 35/60/35/50Sh supporting construction incl. build-on frame 8sides 70 mm

